

Product profile

PB₂/PB₃

Commercial Mobile Receipt Printers



- Compact and lightweight for all-day use
- Compatible with popular Intermec CN3 Series, 700 Series and CK3 mobile computers
- Long life, field replaceable batteries
- Choice of Bluetooth®, WLAN, or IrDA communications, plus standard Serial
- On-board memory supports resident fonts, logos, graphics
- Optional magnetic stripe reader
- Optional environmental case for adverse conditions

Comfortable enough to wear all day, the lightweight and compact Intermec PB2/PB3 two- and three-inch commercial receipt printers meet the needs of the mobile workforce in DSD/route accounting, retail queue busting and field service applications. Long-lasting, field replaceable batteries and weather-resistant construction ensure the PB2/PB3 delivers dependable, all-day service, whenever and wherever required.

The ideal companion to Intermec world-class mobile computers and scanners, the PB2/PB3 printer interfaces seamlessly via Bluetooth® or 802.11g with the CN3 and 700 Series handheld computers, as well as with the new Intermec CK3. The PB2/PB3 also has the ability to print from a wide range of handheld devices and smart phones to produce receipts on demand. Available with optional card reader, the PB2/PB3 gives workers the flexibility to accept payments via their mobile computer or their printer. Either way, the combination supports increased productivity and customer satisfaction, enabling workers to process payments on the go and generate receipts immediately.

The PB2/PB3 and its accessories are designed for easy mobility. The most compact and lightweight of Intermec's

mobile printers, the PB2/PB3 can be comfortably worn all day, using the included belt clip or optional shoulder strap for convenient, hands-free operation. For added protection in outdoor applications such as issuing electronic citations and processing car rental returns, the PB2/PB3 offers an optional IP54-rated environmental case that provides extra weather resistance without affecting mobility.

With multiple connectivity options and robust, field-replaceable batteries, the PB2/PB3 is always ready to work. Batteries can be charged independently of the printer unit, maximizing uptime and convenience. And the PB2/PB3 comes with secure Bluetooth, 802.11 or IrDA wireless connectivity, as well as standard serial communication.

Priced affordably to enable efficient, cost-effective receipt printing where and when it's needed, the PB2/PB3 commercial receipt printers help companies increase the return on their mobility investment. The PB2/PB3 printers are part of a complete hardware solution from Intermec, that also includes Intermec receipt media and Medallion Support services, as well as a full range of AIDC products.



www.amlabels.co.uk
sales@amlabels.co.uk
01536 414222



Physical Characteristics

	PB2	PB3
Width	103.23 mm (4.06 in)	127.20 mm (5.01 in)
Height	60.96 mm (2.40 in)	57.69 mm (2.27 in)
Length	138.58 mm (5.46 in)	156.10 mm (6.14)
Weight – printer only	314 g (11.1 oz)	422 g (14.9 oz)
Weight – with battery & media roll	472 g (16.7 oz)	583 g (20.6 oz)

Environmental

Operating temperature: -10°C to 50°C (14°F to 122°F)
Storage temperature: -20°C to 60°C (-4°F to 140°F) without battery
Operating humidity: 20% to 85% non-condensing
Storage humidity: 5% to 95% non-condensing
Rain & Dust Resistance: IP54 with optional environmental case
Drop spec: Survives 1.5m (5 ft.) drop to concrete

Power

Battery: Rechargeable 7.4V Li-Ion, 2200mAh. Battery rechargeable up to 8.5V.
Recharging: approximately 180 minutes
Charging temperature: 10°C to 25°C (68°F to 77°F)
Battery storage temperature: 4°C to 40°C (40°F to 104°F)
Endurance per fully charged battery at 25% print density: 10% print density: PB2: 127m (415 ft); PB3: 108m (354 ft).
AC Adapter: 100 to 240 VAC @0.4A; meets CEC EPS

Memory

RAM: 1MB
Flash: 4MB

Standard Communications

RS-232 Serial

Optional Communications

Bluetooth® (v2.0, Class II)
IrDA
802.11g

Wireless Security

Authentication and Encryption Options: WPA-PSK/WPA2-PSK; LEAP; WEP 64/WEP 128; TKIP and AES/CCMP

Optional Card Reader

Magnetic Stripe Reader (MSR) 3 track - ANSI/ISO 7810, 7811 standards

Print Speed and Resolution

203 dpi (8 dots/mm)
PB2: up to 2+ ips (56mm/s at 7.2V; 25C and 64 dots fired) at 8.5V
PB3: up to 2 ips (50mm/s at 7.2V; 25C and 64 dots fired) at 8.5V

Print Technology

Printhead: Direct thermal
Maximum print width: **PB2:** 48mm (1.89 in); **PB3:** 72mm (2.83 in)

Media

Type: Receipt media
Width: **PB2:** 57mm (2.25 in); **PB3:** 79mm (3.125 in)
Media length: Continuous
Thickness: up to 4 mil
Core ID: 10mm (0.4 in)
Capacity: **PB2:** 18m (60 ft); **PB3:** 13m (44 ft)

Software

Programming Language
ESC-P command sets (Line Print and Easy Print modes)

Character Sets

Standard: English and Latin
Optional: Arabic, Simplified Chinese, Traditional Chinese, Cyrillic, Greek, Hebrew, and Polish
Resident font sizes: PB2: 24, 32,38,40, 48 characters per line; PB3: 36, 48, 57, 63, 72 characters per line

Graphics

Supports user-defined fonts, graphics, formats and layouts, including custom logos

Barcode Symbolologies

1D: Codabar, Code 39, Code 128 Subset A-C, UCC/EAN-128, Interleaved 2 of 5, UPC/EAN/JAN
2D: PDF417

User Interface

Three Multi-function Status LEDs: Power on, Bluetooth® or 802.11g radio on, low battery, battery charging, card reader ready (for MSR options), print error, paper out.

Ships with

Printer, battery, universal AC adapter, belt clip, one roll of media, printhead cleaning pen, quick start users guide

Accessories

Universal AC charger with four socket adapter plugs, belt clip, shoulder strap, IP54 protective environmental case, card reader cleaning cards, printhead cleaning pen, battery, two-bay battery charger, cigarette lighter adapter/12V vehicle battery charger, serial cable, developers kit.

Warranty

One year; additional Medallion service packages available

North America

Corporate Headquarters
6001 36th Avenue West
Everett, Washington 98203
Phone: (425) 348-2600
Fax: (425) 355-9551

South America & Mexico

Headquarters Office
Newport Beach, California
Phone: (949) 955-0785
Fax: (949) 756-8782

Europe/Middle East &

Africa Headquarters Office
Reading, United Kingdom
Phone: +44 118 923 0800
Fax: +44 118 923 0801

Asia Pacific

Headquarters Office
Singapore
Phone: +65 6303 2100
Fax: +65 6303 2199

Internet

www.intermec.com
Worldwide Locations:
www.intermec.com/locations

Sales

Toll Free NA: (800) 934-3163
Toll in NA: (425) 348-2726
Freephone ROW: 00 800 4488 8844
Toll ROW: +44 134 435 0296

OEM Sales

Phone: (425) 348-2762

Media Sales

Phone: (513) 874-5882

Customer Service and Support

Toll Free NA: (800) 755-5505
Toll in NA: (425) 356-1799

Copyright © 2008 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611906-01D 11/08



In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.