



Web: www.amlabels.co.uk
E-mail: sales@amlabels.co.uk

Tel: 01536 414222
Fax: 01536 414333

FASSON DEMAND JET GLOSS 90 WHITE REMOVABLE

Facestock

A white, high gloss, coated paper with a micro-porous and highly absorbent surface structure, specifically designed for use in Primera and VIP Color Technologies' on demand ink jet printers.

Basis weight : 95 g/m² ISO 536
Caliper : 0.110 mm ISO 534
Gloss : 76% TAPPI-480 @ 76°

Adhesive

Removable adhesive featuring good tack and adhesion performance in combination with superior and clean removability.

Liner

BG40 White, a super calendared glassine paper

Basis Weight : 60 g/m² ISO 536
Caliper : 0.055 mm ISO 534
Transparency : 45% Min DIN 53147

Laminate

Total Caliper 0.180 mm +/-10%

PERFORMANCE DATA

Typical Values

Stainless Steel
Peel Adhesion : 350 N/M FTM 2

Quick Stick : 700 N/M FTM 9
Glass

Minimum Applic.temperature : 0°C
Service temperature : -20°C / +80°C

Adhesive Performance

Removable adhesive featuring good tack and adhesion performance in combination with superior and clean removability. It retains removability at fairly low temperatures.

Applications and use

Demand Jet Gloss is an ideal choice for printing labels on the Primera LX400, LX800, VP2020 and VP485 digital ink jet printers, where full process colour is used to add impact and/or functionality to the label.

The high ink hold out and quick drying provides for excellent clarity and density of printed graphics, making it the perfect choice for primary and secondary packaging labels.

LABEL PRINTING SYSTEMS – BARCODING SYSTEMS – LABELS & THERMAL RIBBONS

AM Labels Ltd – Registered in England No. GB 3163055

Unit G, Northfield Point, Cunliffe Drive, Kettering, Northants, NN16 9QJ



Printing and converting

The product is designed to be converted and by all conventional roll to roll technologies

Automatic Application

The product is designed to apply on high speed automatic roll applicators.

Shelf life

Two years when stored at 22 °C / 50% R.H.

Web: www.amlabels.co.uk
E-mail: sales@amlabels.co.uk

Tel: 01536 414222
Fax: 01536 414333